




mini
KENDrill

Broca de metal duro integral, serie larga 15xD, con refrigeración interna
Solid carbide twist drill, long serie 15xD, with internal cooling
Foret en carbure monobloc, série longue 15xD, avec trous de lubrification
Punta en metallo duro, serie lunga 15xD, con canali di refrigerazione
Hochleistungsbohrer VHM mit Innenkühlung, lang, Ausführung bis zu 15xD
Цельные твердосплавные сверла, длинная серия 15xD, с внутренним подводом СОЖ

R215.5D

K
DRILL



D	d	l	L	R215.5D
h7	h6			
1,4	4	25	62	00140
1,5	4	27	62	00150
1,6	4	29	62	00160
1,7	4	31	70	00170
1,8	4	32	70	00180
1,9	4	34	70	00190
2	4	36	70	00200
2,1	4	38	78	00210
2,2	4	40	78	00220
2,3	4	42	78	00230
2,4	4	44	78	00240
2,5	4	45	78	00250
2,6	4	47	87	00260
2,7	4	48	87	00270
2,8	4	50	87	00280
2,9	4	52	87	00290
3	4	54	87	00300



Condiciones de corte
Cutting conditions
Conditions de coupe
Condizioni di taglio
Schnittbedingungen
Режимы резания

R215.5D

Acero Steel <1400 N/mm ²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 5÷50 HRc	Acero Steel 50÷70 HRc
😊	😊	😊	🎯				😊	😊		

[illegible]

[illegible]

[illegible]

[illegible]