




Broca de metal duro integral, serie extra larga 25xD, con refrigeración interna
Solid carbide twist drill, extra long serie 25xD, with internal cooling
Foret en carbure monobloc, série extra longue 25xD, avec trous de lubrification
Punta en metallo duro, serie extra lunga 25xD, con canali di refrigerazione
Hochleistungsbohrer VHM mit Innenkühlung, extra lang, Ausführung 25xD
Цельные твердосплавные сверла, экстрa длинная серия 25xD, с внутренним подводом СОЖ

**K
DRILL**



N
TYP



D	d	I	L	L4	R225.6D.
h7	h6				
3	6	85	125	36	00300
3,5	6	116	156	36	00350
4	6	116	156	36	00400
4,5	6	143	183	36	00450
5	6	143	183	36	00500
5,5	6	170	210	36	00550
6	6	170	210	36	00600
6,5	8	197	237	36	00650
7	8	197	237	36	00700
7,5	8	223	237	36	00750
8	8	223	263	36	00800
8,5	10	250	294	40	00850
9	10	250	294	40	00900
10	10	250	294	40	01000
12	12	337	386	45	01200



Condiciones de corte
Cutting conditions
Conditions de coupe
Condizioni di taglio
Schnittbedingungen
Режимы резания

Acero Steel ≤1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 5÷50 HRC	Acero Steel 50÷70 HRC

