




Steelken




DIN 845-B NORM  
DIN 228-A  
Brillante Uncoated

HSSE Co 8

SERIE N


N TYP

30° HELIX



Fresa frontal, varios labios - Cono Morse  
Multi flute end mill - Morse taper  
Fraise cylindrique en bout, multident - Cône Morse  
Fresa cilindrìche frontali, multidenti - Cono Morse  
Schafftfräser, Mehrschneiden - Morsekegel  
Фреза многозубая, хвостовик с конусом Морзе

D	CM	I	L	Z	212.80.
k10					
14	2	26	111	4	01400
15	2	26	111	4	01500
16	2	32	117	4	01600
18	2	32	117	4	01800
20	2	38	123	4	02000
22	2	38	123	6	02200
24	3	45	147	6	02400
25	3	45	147	6	02500
26	3	45	147	6	02600
28	3	45	147	6	02800
30	3	45	147	6	03000
32	4	53	178	6	03200
34	4	53	178	6	03400
36	4	53	178	6	03600
38	4	63	188	6	03800
40	4	63	188	6	04000
45	4	63	188	8	04500
50	5	75	233	8	05000
63	5	90	248	8	06300



↓

Condiciones de corte  
Cutting conditions  
Conditions de coupe  
Condizioni di taglio  
Schnittbedingungen  
Режимы резания

212.80										
Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 45÷50 HRc	Acero Steel 50÷70 HRc
😊	😊	😊		😊			😊	😊		









[illegible]

