



uni  
KenGraf



HM  
MG 6

R ±0,02

KENDU  
NORM


SERIE  
N

N  
TYP

HSC


30°  
HELIX

DIN  
6535-HA



Fresa frontal punta semiesférica, 4 labios  
4 flute ball nose end mill  
Fraise cylindrique à bout hémisphérique, 4 dents  
Fresa cilindriche frontali a testa semisferica, 4 denti  
Kugelfräser, 4 Schneiden  
Фреза 4-х зубая с полусферическим торцом

D	d	I	L	Z	R	2900.26.
h9	h6				±0,02	
4	4	12	40	4	2	00400
5	5	14	50	4	2,5	00500
6	6	16	50	4	3	00600
8	8	20	60	4	4	00800
10	10	22	70	4	5	01000
12	12	25	75	4	6	01200



Condiciones de corte  
Cutting conditions  
Conditions de coupe  
Condizioni di taglio  
Schnittbedingungen  
Режимы резания

2900.26										
Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 45÷50 HRc	Acero Steel 50÷70 HRc
						😊				

