



mini  
KENDrill

Broca de metal duro integral, serie hasta 4xD  
Solid carbide twist drill, serie up to 4xD  
Foret en carbure monobloc, série jusqu'à 4xD  
Punta en metallo duro, serie fino 4xD  
Hochleistungsbohrer VHM, Ausführung bis zu 4xD  
Цельные твердосплавные сверла, серия вплоть до 4xD

B204.5D

K  
DRILL



HM  
SM


KENDU  
NORM

N  
TYP



DIN  
6535-HA

30°  
HELIX



D	d	l	L	B204.5D.
m7	h6			
0,5	3	3	47	00050
0,6	3	4	47	00060
0,7	3	4	47	00070
0,8	3	5	47	00080
0,9	3	5	47	00090
1	3	6	47	00100
1,1	3	7	47	00110
1,2	3	7	47	00120
1,3	3	8	47	00130
1,4	3	8	47	00140
1,5	3	9	47	00150
1,6	3	10	47	00160
1,7	3	10	47	00170
1,8	3	11	52	00180
1,9	3	11	52	00190
2	4	12	59	00200

D	d	l	L	B204.5D.
m7	h6			
2,1	4	13	59	00210
2,2	4	13	59	00220
2,3	4	14	59	00230
2,4	4	14	59	00240
2,5	4	15	59	00250
2,6	4	16	59	00260
2,7	4	16	59	00270
2,8	4	17	59	00280
2,9	4	17	59	00290
3	4	18	59	00300

Condiciones de corte  
Cutting conditions  
Conditions de coupe  
Condizioni di taglio  
Schnittbedingungen  
Режимы резания

B204.5D

Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 5÷50 HRc	Acero Steel 50÷70 HRc
😊	😊	😊	🎯				😊	😊		

[illegible]





[illegible]

[illegible]

